OIPE
DEC 0 3 2001
JC48
PATENT & TRADEMARK OFFICE

Clean Version of the Amended Claims

1.   (Amended) A speech coding apparatus including at least:

a spectrum parameter calculation section for receiving a speech signal, obtaining a spectrum parameter, and quantizing the spectrum parameter,

an adaptive codebook section for obtaining a delay and a gain from a past quantized sound source signal by using an adaptive codebook, and obtaining a residue by predicting a speech signal, and

a sound source quantization section for quantizing a sound source signal of the speech signal by using the spectrum parameter and outputting the sound source signal, comprising:

a discrimination section for discriminating a voiced sound mode and an unvoiced sound mode on a basis of a past quantized gain of an adaptive codebook;

a sound source quantization section which has a codebook for representing a sound source signal by a combination of a plurality of non-zero pulses and collectively quantizing amplitudes or polarities of the pulses based on an output from said discrimination circuit section, and searches combinations of code vectors stored in said codebook and a plurality of shift amounts used to shift positions of the pulses so as to output a combination of a code vector and shift amount which minimizes distortion relative to input speech; and

a multiplexer section for outputting a combination of an output from said spectrum parameter calculation section, an output from said adaptive codebook section, and an output from said sound source quantization section.

2.   (Amended) A speech-coding apparatus including at least:

a spectrum parameter calculation section for receiving a speech signal, obtaining a spectrum parameter, and quantizing the spectrum parameter,

an adaptive codebook section for obtaining a delay and a gain from a past quantized sound source signal by using an adaptive codebook, and obtaining a residue by predicting a speech signal, and

a sound source quantization section for quantizing a sound source signal of the speech signal by using the spectrum parameter and outputting the sound source signal, comprising:

a discrimination section for discriminating a voice sound mode and an unvoiced sound mode on a basis of a past quantized gain of an adaptive codebook;

a sound source quantization section which has a codebook for representing a sound source signal by a combination of a plurality of non-zero pulses and collectively quantizing amplitudes or polarities of the pulses based on an output from said discrimination section, and outputs a code vector that minimizes distortion relative to input speech by generating positions of the pulses according to a predetermined rule; and

a multiplexer section for outputting a combination of an output from said spectrum parameter calculation section, an output from said adaptive codebook section, and an output from said sound source quantization section

3.   (Amended) A speech coding apparatus including at least:

a spectrum parameter calculation section for receiving a speech signal, obtaining a spectrum parameter, and quantizing the spectrum parameter,

an adaptive codebook section for obtaining a delay and a gain from a past quantized sound source signal by using an adaptive codebook, and obtaining a residue by predicting a speech signal, and

a sound source quantization section for quantizing a sound source signal of the speech signal by using the spectrum parameter and outputting the sound source signal, comprising:

a discrimination section for discriminating a voice sound mode and an unvoiced sound mode on the basis of a past quantized gain of an adaptive codebook;

a sound source quantization section which has a codebook for representing a sound source signal by a combination of a plurality of non-zero pulses and collectively quantizing amplitudes or polarities of the pulses based on an output from said discrimination section, and a gain codebook for quantizing gains, and searches combinations of code vectors stored in said codebook, a plurality of shift amounts used to shift positions of the pulses, and gain code vectors stored in said gain codebook so as to output a combination of a code vector, shift amount, and gain code vector which minimizes distortion relative to input speech; and

a multiplexer section for outputting a combination of an output from said spectrum parameter calculation section, an output from said adaptive codebook section, and an output from said sound source quantization section.

4.   (Amended) A speech coding apparatus including at least:

a spectrum parameter calculation section for receiving a speech signal, obtaining a spectrum parameter, and quantizing the spectrum parameter,

an adaptive codebook section for obtaining a delay and a gain from a past quantized sound source signal by using an adaptive codebook, and obtaining a residue by predicting a speech signal, and

a sound source quantization section for quantizing a sound source signal of the speech signal by using the spectrum parameter and outputting the sound source signal, comprising:

a discrimination section for discriminating a voice sound mode and an unvoiced sound mode on the basis of a past quantized gain of a adaptive codebook;

a sound source quantization section which has a codebook for representing a sound source signal by a combination of a plurality of non-zero pulses and collectively quantizing amplitudes or polarities of the pulses based on output from said discrimination section, and a gain codebook for quantizing gains, and outputs a combination of a code vector and gain code vector which minimizes distortion relative to input speech by generating positions of the pulses according to a predetermined rule; and

a multiplexer section for outputting a combination of an output from said spectrum parameter calculation section, an output from said adaptive codebook section, and an output from said sound source quantization section.

5. (Amended) A speech decoding apparatus comprising:

a demultiplexer section for receiving and demultiplexing a spectrum parameter, a delay of an adaptive codebook, a quantized gain, and quantized sound source information;

a mode discrimination section for discriminating a voice sound mode and an unvoiced sound mode by using a past quantized gain in said adaptive codebook; and

a sound source signal reconstructing section for reconstructing a sound source signal by generating non-zero pulses from the quantized sound source information based on an output from said discrimination section,

wherein a speech signal is reproduced by passing the sound source signal through a synthesis filter section which includes spectrum parameters.

6. (Amended) A speech coding/decoding apparatus comprising:

a speech coding apparatus including:

a spectrum parameter calculation section for receiving a speech signal, obtaining a spectrum parameter, and quantizing the spectrum parameter,

an adaptive codebook section for obtaining a delay and a gain from a past quantized sound source signal by using an adaptive codebook, and obtaining a residue by predicting a speech signal,

a sound source quantization section for quantizing a sound source signal of the speech signal by using the spectrum parameter and outputting the sound source signal,

a discrimination section for discriminating a voice sound mode and an unvoiced sound mode on the basis of a past quantized gain of a adaptive codebook, and

a codebook for representing a sound source signal by a combination of a plurality of non-zero pulses and collectively quantizing amplitudes or polarities of the pulses when an output from said discrimination section indicates a predetermined mode,

said sound source quantization section searching combinations of code vectors stored in said codebook and a plurality of shift amounts used to shift positions of the pulses so as to poutout a combination of a code vector and shift amount which minimizes distortion relative to input speech, and further including:

a multiplexer section for outputting a combination of an output from said spectrum parameter calculation section, an output from said adaptive codeboook section, and an output from said sound source quantization section; and

a speech decoding apparatus including at least:

a demultiplexer section for receiving and demultiplexing a spectrum parameter, a delay of an adaptive codebook, a quantized gain, and quantized sound source information,

a mode discrimination section for discriminating a mode by using a past quantized gain in said adaptive codebook,

a sound source signal reconstructing section for reconstructing a sound source signal by generating non-zero pulses from the quantized sound source information when an output from said discrimination indicates a predetermined mode, and

a synthesis filter section which is constituted by spectrum parameters and reproduces a speech signal by filtering the sound source signal.

7.   (Amended) A speech coding/decoding apparatus comprising:

a speech coding apparatus including:

a spectrum parameter calculation section for receiving a speech signal, obtaining a spectrum parameter, and quantizing the spectrum parameter,

an adaptive codebook section for obtaining a delay and a gain from a past quantized sound source signal by using an adaptive codebook, and obtaining a residue by predicting a speech signal,

a sound source quantization section for quantizing a sound source signal of the speech signal by using the spectrum parameter and outputting the sound source signal,

a discrimination section for discriminating a voice sound mode and an unvoiced sound mode on the basis of a past quantized gain of a adaptive codebook, and

a codebook for representing a sound source signal by a combination of a plurality of non-zero pulses and collectively quantizing amplitudes or polarities of the pulses based on an output from said discrimination section,

said sound source quantization section for outputting a combination of a code vector and shift amount which minimizes distortion relative to input speech by generating positions of the pulses according to a predetermined rule, and further including

a multiplexer section for outputting a combination of an output from said spectrum parameter calculation section, an output from said adaptive codebook section, and an output from said sound source quantization section; and

a speech decoding apparatus including at least:

a demultiplexer section for receiving and demultiplexing a spectrum parameter, a delay of an adaptive codebook, a quantized gain, and quantized sound source information,

a mode discrimination section for discriminating a mode by using a past quantized gain in said adaptive codebook,

a sound source signal reconstructing section for reconstructing a sound source signal by generating positions of pulses according to a predetermined rule and generating amplitudes or polarities for the pulses from a code vector when an output from said discrimination section indicates a predetermined mode, and

a synthesis filter section which includes spectrum parameters and reproduces a speech signal by filtering the sound source signal.